

L5 ANSWER 7 OF 28 CA COPYRIGHT 2005 ACS on STN

AN 132:297574 CA

ED Entered STN: 19 May 2000

TI **Setting delay agent for cement**  
paste.

IN Nedelcu, Constantin; Stadler, Petre; Baleanu, Ion

PA PETROM R.A. - Institutul de Cercetari si Proiectari Tehnologice, Campina,  
Rom.

SO Rom., 4 pp.

CODEN: RUXXA3

DT Patent

LA Romanian

IC ICM C04B007-06

ICS C09K007-00

CC 58-1 (Cement, Concrete, and Related Building Materials)

FAN.CNT 1

	PATENT NO.	KIND	DATE	APPLICATION NO.	DATE
PI	RO 111757	B1	19970130	RO 1994-2117	19941228
PRAI	RO 1994-2117		19941228		

CLASS

PATENT NO.	CLASS	PATENT FAMILY CLASSIFICATION CODES
RO 111757	ICM	C04B007-06
	ICS	C09K007-00
RO 111757	ECLA	C04B040/00D4; C09K008/46

AB **Setting delay agent for cement**  
paste used mainly in construction of high-temperature petroleum well  
construction consists. of lignosulfonate waste 370 L, sodium hydroxide 51  
kg, tartrates and formic aldehyde.

ST **setting delay agent cement** paste

IT **Cement** (construction material)  
(paste; **setting delay agent for**  
**cement** paste.)

IT Hardening (mechanical)  
(**setting; setting delay agent**  
for **cement** paste.)

IT 50-00-0, Formic aldehyde, uses 87-6